

EMC Test Report

Report No.: AGC05443220427EE01

PRODUCT DESIGNATION: LED flashlight in aluminium

BRAND NAME : N/A

MODEL NAME : MO6591

APPLICANT: MID OCEAN BRANDS B.V

DATE OF ISSUE : Apr. 19, 2022

STANDARD(S) : EN IEC 55015:2019+A11:2020

EN 61547:2009

REPORT VERSION: V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd





Page 2 of 36

REPORT REVISE RECORD

Report Version	Revise Time	Issued Date	Issued Date Valid Version	
V1.0	/	Apr. 19, 2022	Valid	Initial release






TABLE OF CONTENTS

1 VERIFICATION OF CONFORMITY	5
2 SYSTEM DESCRIPTION	6
3 MEASUREMENT UNCERTAINTY	6
4 PRODUCT INFORMATION	7
5 SUPPORT EQUIPMENT	8
6 TEST FACILITY	9
7 TEST EQUIPMENT LIST	9
8 TEST SUMMARY LIST	11
9 EN IEC 55015 RADIATED EMISSION TEST	12
9.1 LIMITS OF RADIATED DISTURBANCES	12
9.2 BLOCK DIAGRAM OF TEST SETUP	12
9.3 PROCEDURE OF RADIATED EMISSION TEST	13
9.4 TEST RESULT OF RADIATED EMISSION TEST	14
10 EN IEC 55015 RADIATED ELECTROMAGNETIC DISTURBANCE TEST	16
10.1 LIMITS OF RADIATED ELECTROMAGNETIC DISTURBANCE IN THE RANGE 9 KHZ TO 30 MHZ	16
10.2 BLOCK DIAGRAM OF TEST SETUP	17
10.3 TEST PROCEDURE	17
10.4 TEST RESULTS OF RADIATED ELECTROMAGNETIC DISTURBANCE	18
11 EN 61000-4-2 ESD IMMUNITY TEST	21
11.1 BLOCK DIAGRAM OF TEST SETUP	21
11.2 TEST PROCEDURE	22
11.3 PERFORMANCE & RESULT	23
12 EN 61000-4-3 RS IMMUNITY TEST	24
12.1 BLOCK DIAGRAM OF TEST SETUP	24
12.2 TEST PROCEDURE	25
12.3 PERFORMANCE & RESULT	26



Report No.: AGC05443220427EE01 Page 4 of 36

13 EN 61000-4-8 PFMF TEST	27
13.1 BLOCK DIAGRAM OF TEST SETUP	27
13.2 TEST PROCEDURE	28
13.3 PERFORMANCE & RESULT	28
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	29
APPENDIX B. PHOTOGRAPHS OF FUT	32



Report No.: AGC05443220427EE01 Page 5 of 36

1 VERIFICATION OF CONFORMITY

Applicant	MID OCEAN BRANDS B.V
Address	7/F, Kings Tower, 111 King Lam Street, Cheung Sha Wan, Kowloon, Hong Kong
Manufacturer	MID OCEAN BRANDS B.V
Address	7/F, Kings Tower, 111 King Lam Street, Cheung Sha Wan, Kowloon, Hong Kong
Factory	MID OCEAN BRANDS B.V
Address	7/F, Kings Tower, 111 King Lam Street, Cheung Sha Wan, Kowloon, Hong Kong
Product Designation	LED flashlight in aluminium
Brand Name	N/A
Test Model	MO6591
Date of test	Apr. 14, 2022 to Apr. 19, 2022
Deviation	No deviation from the test method.
Condition of Test Sample	Normal
Test Result	Pass
The state of the s	(1) (1) (1) (1) (1) (1) (1) (1) (1) (1)

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. for compliance with the requirements set forth in the Technical Standards mentioned above. This said equipment in the configuration described in this report shows the maximum emission levels emanating from equipment and the level of the immunity endurance of the equipment are within the compliance requirements.

The test results of this report relate only to the tested sample identified in this report.

Prepared By	Jouk Gai	
	Jack Gui (Project Engineer)	Apr. 19, 2022
Reviewed By	Calin Lin	
	Calvin Liu (Reviewer)	Apr. 19, 2022
Approved By	Forrest Wi	
	Forrest Lei (Authorized Officer)	Apr. 19, 2022



Page 6 of 36

2 SYSTEM DESCRIPTION

	TEST MODE DESCRIPTION					
NO.	TEST MODE DESCRIPTION	WORST				
1.	Steady light mode (100% brightness)	V				
2.	Flash light mode					
	1. V means EMI worst mode.					

3 MEASUREMENT UNCERTAINTY

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in measurement" (GUM) published by ISO.

- Uncertainty of Radiated Emission, Uc = ±3.8dB



Page 7 of 36

4 PRODUCT INFORMATION

Housing Type	Plastic and metal
EUT Input Rating	DC 4.5V by battery
Hardware Version	N/A
Software Version	N/A

I/O Port Information (☐Applicable ☐Not Applicable)

I/O Port of EUT					
I/O Port Type Number Cable Description Tested With					



Page 8 of 36

5 SUPPORT EQUIPMENT

Device Type	Manufacturer	Model Name	Serial No.	Data Cable	Power Cable

Note:. "-- " means no any support device during testing.



Page 9 of 36

6 TEST FACILITY

Site	Attestation of Global Compliance (Shenzhen) Co., Ltd
Location	1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao 'an District, Shenzhen, Guangdong, China

7 TEST EQUIPMENT LIST

TEST EQUIPMENT OF RADIATED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Test Receiver	R&S	ESCI	10096	Mar. 28, 2022	Mar. 27,2023
Antenna	SCHWARZBECK	VULB9168	494	Jan. 08, 2021	Jan. 07, 2023
Test software	FARA	EZ-EMC (Ver.RA-03A)	N/A	N/A	N/A

TEST EQUIPMENT OF RADIATED ELECTROMAGNETIC DISTURBANCE TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Triple Loop Antenna	LAPLACE	RF300	9070	Jul. 26, 2021	Jul. 25, 2022
Test Receiver	R&S	ESCI	10096	May. 15, 2020	May. 14, 2022

TEST EQUIPMENT OF ESD TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
ESD Simulator	Schaffner	NSG 438	782	Jan. 08, 2022	Jan. 07, 2023



Page 10 of 36

TEST EQUIPMENT OF RS IMMUNITY TEST

Description	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Signal Generator	R&S	E4421B	MY43351603	May. 11, 2021	May .10, 2022
Power Sensor	R&S	URV5-Z4	100124	Apr. 26, 2021	Apr. 25, 2023
Power Meter	R&S	NRVD	8323781027	Apr. 26, 2021	Apr. 25, 2023
Power Amplifier	KALMUS	7100LC	04-02/17-06-00 1	N/A	N/A
Power Amplifier	Milmega	AS0104-55_55	1004793	N/A	N/A
Broadband Preamplifier	SCHWARZBEC K	VULB9168	D69250	N/A	N/A

TEST EQUIPMENT OF PFMF TEST

Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
PFMF system	HTEC	HPFMF	161701	Jul. 02, 2021	Jul. 01, 2022



Page 11 of 36

8 TEST SUMMARY LIST

Test item	Test Requirement	Test Method	Class/Severity	Result
CONDUCTED EMISSION	EN IEC 55015	EN IEC 55015	0.009MHz -30MHz	N/A
RADIATED EMISSION	EN IEC 55015	EN IEC 55015	30MHz -1000MHz	Pass
RADIATED ELECTROMAGNETIC DISTURBANCE	EN IEC 55015	EN IEC 55015	0.009MHz -30MHz	Pass
Harmonic current emission	EN IEC 61000-3-2	EN IEC 61000-3-2	Class C	N/A
Voltage fluctuations & flicker	EN 61000-3-3	EN 61000-3-3	§5 of EN 61000-3-3	N/A
Electrostatic Discharge Immunity	EN 61547	EN 61000-4-2	± 8.0 kV (Air Discharge) ± 4.0 kV (Contact Discharge) ± 4.0 kV (Indirect Discharge)	Pass
Radiated RF Electromagnetic	EN 61547	EN 61000-4-3	3V/m with 80% AM. 1kHz Modulation.	Pass
Electrical fast transient/burst Immunity	EN 61547	EN 61000-4-4	+/- 1kV for Power Supply Lines	N/A
SURGE IMMUNITY	EN 61547	EN 61000-4-5	>25W +/-1kV (Line to Line) +/-2kV (Line to Ground) <25W +/-0.5kV (Line to Line) +/-1kV (Line to Ground)	N/A
Immunity to Conducted Disturbances Induced by RF fields	EN 61547	EN 61000-4-6	3V with 80% AM. 1 kHz Modulation	N/A
Power Frequency Magnetic Fields	EN 61547	EN 61000-4-8	50/60 Hz, 3A/m	Pass
Voltage dips and short interruptions immunity	EN 61547	EN 61000-4-11	PHASE ANGLE 0, 45, 90, 135, 180, 225, 270, 315 degrees	N/A



Page 12 of 36

9 EN IEC 55015 RADIATED EMISSION TEST

9.1 LIMITS OF RADIATED DISTURBANCES

AT 10M DISTANCES

Frequency (MHz)	Distance (m)	Maximum Field Strength Limit (dBuV/m Q.P.)
30-230	10	30.00
230-1000	10	37.00


AT 3M DISTANCES

Frequency (MHz)	Distance (m)	Maximum Field Strength Limit (dBuV/m Q.P.)
30-230	3	40.00
230-1000	3	47.00

Note: The lower limit shall apply at the transition frequency.

9.2 BLOCK DIAGRAM OF TEST SETUP

System Diagram of Connections between EUT and Simulators





Page 13 of 36

9.3 PROCEDURE OF RADIATED EMISSION TEST


- (1) The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden turntable with a height of 0.8 meters is used which is placed on the ground plane as per EN IEC 55015 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 10cm non-conductive covering to insulate the EUT from the ground plane.
- (2) Support equipment, if needed, was placed as per EN IEC 55015.
- (3) All I/O cables were positioned to simulate typical actual usage as per EN IEC 55015.
- (4) The EUT was turned on.
- (5) The antenna was placed at 3 meters away from the EUT as stated in EN IEC 55015. The antenna connected to the Analyzer via a cable and at times a pre-amplifier would be used.
- (6) The Analyzer / Receiver quickly scanned from 30MHz to 1000MHz. The EUT test program was started. Emissions were scanned and measured rotating the EUT to 360 degrees and positioning the antenna 1 to 4 meters above the ground plane, in both the vertical and the horizontal polarization, to maximize the emission reading level.
- (7) The test mode(s) were scanned during the test:
- (8) Recorded at least the six highest emissions. Emission frequency, amplitude, antenna position, polarization and turntable position were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit and Q.P./Peak reading is presented.



Page 14 of 36


9.4 TEST RESULT OF RADIATED EMISSION TEST

Radiated Emission Test at 3m Distance-Horizontal



Frequency[MHz]	Level[dBµV/m]	Factor[dB]	Limit[dBµV/m]	Margin[dB]	Detector	Polarity
40.7016	21.60	15.99	40.00	18.4	peak	Horizontal
68.8721	24.18	18.04	40.00	15.82	peak	Horizontal
125.0066	25.29	18.89	40.00	14.71	peak	Horizontal
325.5958	30.34	24.25	47.00	16.66	peak	Horizontal
383.9318	31.02	23.80	47.00	15.98	peak	Horizontal
972.3374	34.83	28.94	47.00	12.17	peak	Horizontal

RESULT: PASS





Radiated Emission Test at 3m Distance-Vertical



Frequency[MHz]	Level[dBµV/m]	Factor[dB]	Limit[dBµV/m]	Margin[dB]	Detector	Polarity
32.7486	22.66	13.25	40.00	17.34	peak	Vertical
61.9951	23.79	17.92	40.00	16.21	peak	Vertical
125.0066	26.60	19.04	40.00	13.4	peak	Vertical
383.9318	27.62	20.06	47.00	19.38	peak	Vertical
638.3686	31.92	26.03	47.00	15.08	peak	Vertical
968.9338	36.11	29.96	47.00	10.89	peak	Vertical

RESULT: PASS



Page 16 of 36

10 EN IEC 55015 RADIATED ELECTROMAGNETIC DISTURBANCE TEST

10.1 LIMITS OF RADIATED ELECTROMAGNETIC DISTURBANCE IN THE RANGE 9 KHZ TO 30 MHZ

Frequency Range	Limits for Loop Diameter dB(uA) *				
requestey trailige	2m	3m	4m		
9 KHz-70 KHz	88 *	81 *	75 *		
70 KHz-150 KHz	88 to 58 * *	81 to 51 * *	75 to 45 * *		
150 kHz-3.0 MHz	58 to 22 * *	51 to 15 * *	45 to 9 * *		
3.0 MHz-30 MHz	22 * * *	15 to 16 * * *	9 to 12 * * *		


Note:

- * At the transition frequency, the lower limit applies.
- * Decreasing linearly with the logarithm of the frequency. For electrode less lamps and luminaries, the limit in the frequency range of 2.2 MHz to 3.0 MHz is 58 dB(uA) for 2m, 51 dB(uA) for 3m and 45 dB(uA) for 4m loop diameter.
- * * * Increasing linearly with the logarithm of the frequency.



Page 17 of 36

10.2 BLOCK DIAGRAM OF TEST SETUP



10.3 TEST PROCEDURE

The magnetic component shall be measured by means of a loop antenna as described in EN IEC 55015. The lighting equipment shall be placed in the centre of the antenna, and the position is not critical.


The test object was operated at its upper limit of its rated voltage and its rated frequency. The induced current in the loop antenna is measured by means of a current probe(1V/A) and the CISPR measuring receiver. By means of a coaxial switch the three field directions can be measured in sequence. Each value shall fulfill the requirements given.




Page 18 of 36

10.4 TEST RESULTS OF RADIATED ELECTROMAGNETIC DISTURBANCE






Frequency[MHz]	Level[dBµV]	Factor[dB]	Limit[dBµV]	Margin[dB]	Detector	Loop
0.218000	-9.9	-17.0	53.5	63.4	QP	Х
4.278000	-12.1	-26.5	22.0	34.1	QP	Х
4.962000	-13.0	-26.5	22.0	35.0	QP	Х






Υ



Frequency[MHz]	Level[dBµV]	Factor[dB]	Limit[dBµV]	Margin[dB]	Detector	Loop
0.330000	1.6	-20.5	48.5	46.9	QP	Υ
0.618000	-2.6	-24.8	41.0	43.6	QP	Υ
3.590000	-18.8	-26.5	22.0	40.8	QP	Υ



Ζ



Frequency[MHz]	Level[dBµV]	Factor[dB]	Limit[dBµV]	Margin[dB]	Detector	Loop
1.882000	-13.9	-26.3	27.6	41.5	QP	Z
3.846000	-18.3	-26.5	22.0	40.3	QP	Z
4.274000	-15.0	-26.5	22.0	37.0	QP	Z

RESULT: PASS



Page 21 of 36


11 EN 61000-4-2 ESD IMMUNITY TEST

ELECTROSTATIC DISCHARGE (ESD) IMMUNITY TEST

Port	Enclosure
Basic Standard	EN 61000-4-2
Test Level	± 8.0 kV (Air Discharge) ± 4.0 kV (Contact Discharge) ± 4.0 kV (Indirect Discharge)
Standard require	В
Temperature	24.2°C
Humidity	51.0% RH

11.1 BLOCK DIAGRAM OF TEST SETUP

(The 470 k ohm resistors are installed per standard requirement)



Ground Reference Plane₽



Page 22 of 36

11.2 TEST PROCEDURE

The EUT was located 0.1 m minimum from all side of the HCP.

The support units were located 1 m minimum away from the EUT.

EUT worked with resistance load, and make sure EUT worked normally.

Actives the communication function if the EUT with such port(s).

As per the requirement of EN 61547: Contact discharge is the preferred test method, twenty discharges (10 with positive and 10 with negative polarity) shall be applied on each accessible metallic part of the enclosure, terminals are excluded. Air discharges shall be used where contact discharges cannot be applied. Discharges shall be applied on the horizontal or vertical coupling planes as specified in EN 61000-4-2.

The following test condition was followed during the tests.

Note: As per the A2 to EN 61000-4-2, a bleed resistor cable is connected between the EUT and HCP during the test.

The electrostatic discharges were applied as follows:

Voltage	Coupling	Test Performance	Result
±4kV	Contact Discharge	No function loss	A
±4kV	Indirect Discharge HCP (Front)	No function loss	A
±4kV	Indirect Discharge HCP (Left)	No function loss	A
±4kV	Indirect Discharge HCP (Right)	No function loss	A
±4kV	Indirect Discharge HCP (Back)	No function loss	A
±4kV	Indirect Discharge VCP (Front)	No function loss	A
±4kV	Indirect Discharge VCP (Left)	No function loss	A
±4kV	Indirect Discharge VCP (Back)	No function loss	A
±4kV	Indirect Discharge VCP (Right)	No function loss	A
±8kV	Air Discharge	No function loss	A




Page 23 of 36

11.3 PERFORMANCE & RESULT

Criteria A:	The apparatus continues to operate as intended. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance.
Criteria B:	The apparatus continues to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is however allowed.
Criteria C:	Temporary loss of function is allowed, provided the functions self recoverable or can be restored by the operation of controls.

	⊠ PASS	
--	---------------	--






12 EN 61000-4-3 RS IMMUNITY TEST

RADIATED ELECTROMAGNETIC FIELD IMMUNITY TEST

Port	Enclosure
Basic Standard	EN 61000-4-3
Test Level:	3V/m with 80% AM. 1kHz Modulation.
Standard require	A
Temperature	25.0°C
Humidity	55.0% RH

12.1 BLOCK DIAGRAM OF TEST SETUP





Page 25 of 36

12.2 TEST PROCEDURE

The EUT was located at the edge of supporting table keep 3 meter away from transmitting antenna, it just the calibrated square area of field uniformity. The support units were located outside of the uniformity area, but the cable(s) connected with EUT were exposed to the calibrated field as per EN 61000-4-3.

EUT worked with resistance load, and make sure EUT worked normally.

Setting the testing parameters of RS test software per EN 61000-4-3.

Performing the test at each side of with specified level (3V/m) at 1% steps and test frequency from 80MHz to 1000MHz

Recording the test result in following table.

EN 61000-4-3 Final test conditions:

Test level: 3V/m

Steps: 1 % of fundamental

Dwell Time: 1 sec

Range (MHz)	Field	Modulation	Polarity	Position	Test Performance	Result
80-1000	3V/m	AM	Н	Front	No function loss	А
80-1000	3V/m	AM	Н	Left	No function loss	А
80-1000	3V/m	AM	Н	Back	No function loss	А
80-1000	3V/m	AM	Н	Right	No function loss	А
80-1000	3V/m	AM	V	Front	No function loss	А
80-1000	3V/m	AM	V	Left	No function loss	А
80-1000	3V/m	AM	V	Back	No function loss	А
80-1000	3V/m	AM	V	Right	No function loss	А



Page 26 of 36

12.3 PERFORMANCE & RESULT

Criteria A:	The apparatus continues to operate as intended. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance.
Criteria B:	The apparatus continues to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is however allowed.
Criteria C:	Temporary loss of function is allowed, provided the functions self recoverable or can be restored by the operation of controls.

|--|




Page 27 of 36

13 EN 61000-4-8 PFMF TEST

POWER FREQUENCY MAGNETIC FIELDS IMMUNITY TEST

Port	Enclosure
Basic Standard	EN 61000-4-8
Requirements	50/60 Hz, 3A/m
Standard require	А
Temperature	24.3°C
Humidity	54.0% RH

13.1 BLOCK DIAGRAM OF TEST SETUP





Page 28 of 36

13.2 TEST PROCEDURE

The EUT shall be subjected to the test magnetic field by using the induction coil of standard dimensions $(1m \times 1m)$. The induction coil shall then be rotated by 90° in order to expose the EUT to the test field with different orientations.


Test Conditions:

Frequency	Polarity	Level	Test Performance	Performance Result
50 Hz	X	3 A/m	No function loss	Α
50 Hz	Υ	3 A/m	No function loss	А
50 Hz	Z	3 A/m	No function loss	А

13.3 PERFORMANCE & RESULT

Criteria A:	The apparatus continues to operate as intended. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance.
Criteria B:	The apparatus continues to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. In some cases the performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is however allowed.
Criteria C:	Temporary loss of function is allowed, provided the functions self recoverable or can be restored by the operation of controls.


|--|







APPENDIX A: PHOTOGRAPHS OF TEST SETUP

EN IEC 55015 RADIATED EMISSION TEST SETUP




EN IEC 55015 RADIATED ELECTROMAGNETIC DISTURBANCE TEST








EN 61000-4-2 ESD IMMUNITY TEST SETUP




EN 61000-4-3 RS IMMUNITY TEST SETUP






Page 31 of 36

EN 61000-4-8 PFMF TEST SETUP








APPENDIX B: PHOTOGRAPHS OF EUT

TOP VIEW OF EUT



BOTTOM VIEW OF EUT







FRONT VIEW OF EUT




BACK VIEW OF EUT



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/






LEFT VIEW OF EUT



RIGHT VIEW OF EUT









OPEN VIEW OF EUT-1




OPEN VIEW OF EUT-2







INTERNAL VIEW OF EUT



----END OF REPORT----



Conditions of Issuance of Test Reports

- 1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").
- 2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
- 3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
- 4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
- 5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
- 6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
- 7.Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
- 8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
- 9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.