


# TEST REPORT

EN 62471

## Photobiological safety of lamps and lamp systems

<b>Report Number</b> .....	RKEYS251224263
<b>Total number of pages</b> .....	21 pages
<b>Tested by (name + signature)</b> .....	Sunny Li 
<b>Approved by (name + signature)</b> ....	Eason.zeng 
<b>Testing Laboratory Name</b> .....	Guangdong KEYS Testing Technology Co., Ltd.
<b>Address</b> .....	Building 1, No.18, Shihuan Road, Dongcheng Subdistrict, Dongguan, Guangdong, China
<b>Applicant's name</b> .....	Mid Ocean Brands B.V.
<b>Address</b> .....	Unit 711-716, 7/F., Tower A, 83 King Lam Street, Cheung Sha Wan, Kowloon, Hong Kong
<b>Manufacturer's name</b> .....	117486
<b>Address</b> .....	N/A
<b>Test specification:</b>	
<b>Standard</b> .....	EN 62471: 2008
<b>Test procedure</b> .....	Safety report
<b>Non-standard test method</b> .....	N/A
<b>Test item description</b> .....	Torch
<b>Trade Mark</b> .....	N/A
<b>Model/Type reference</b> .....	MO2786
<b>Ratings</b> .....	DC5V

Scan to view  
the original file

**General disclaimer:**

This report is only for applicant use. Any copying this report to/for any other person or entity, and use our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

**List of Attachments:**

Attachment 1: 3 pages of photos.

**Summary of testing:**

The tested samples fulfilled the requirements of specified standards.

**Testing location:**

Guangdong KEYS Testing Technology Co., Ltd.

Building 1, No.18, Shihuan Road, Dongcheng Subdistrict, Dongguan, Guangdong, China

**Summary of compliance with National Differences:**

List of countries addressed: European National Differences.

The product fulfils the requirements of EN 62471:2008.

**Remark:**

/

<b>Test item particulars.....</b> : See test report	
Tested lamp.....	: <input checked="" type="checkbox"/> continuous wave lamps <input type="checkbox"/> pulsed lamps
Tested lamp system.....	: N/A
Lamp classification group.....	: <input type="checkbox"/> exempt <input checked="" type="checkbox"/> risk 1 <input type="checkbox"/> risk 2 <input type="checkbox"/> risk 3
Lamp cap.....	: N/A
Bulb.....	: LED
Rated of the lamp.....	: See page 1
Furthermore marking on the lamp.....	: N/A
Seasoning of lamps according IEC standard.....	: N/A
Used measurement instrument.....	: EN 62471 Tester
<b>Possible test case verdicts:</b>	
- test case does not apply to the test object..... : N/A	
- test object does meet the requirement..... : P (Pass)	
- test object does not meet the requirement.....: F (Fail)	
<b>Testing.....</b> :	
<b>Date of receipt of test item.....</b> : Dec. 24, 2025	
<b>Date (s) of performance of tests.....</b> : Dec. 24, 2025 to Dec. 30, 2025	
<b>General remarks:</b>	
"(See Enclosure #)" refers to additional information appended to the report.	
"(See appended table)" refers to a table appended to the report.	
<b>Throughout this report a <input type="checkbox"/> comma / <input checked="" type="checkbox"/> point is used as the decimal separator.</b>	
<b>General product information:</b>	
1.The appliance/equipment is "Torch " with model "MO2786".	
2.The ambient temperature is 25°C.	

EN 62471			
Clause	Requirement + Test	Result - Remark	Verdict
4	<b>EXPOSURE LIMITS</b>		P
4.1	General		P
	The exposure limits in this standard is not less than 0,01 ms and not more than any 8-hour period and should be used as guides in the control of exposure		P
	Detailed spectral data of a light source are generally required only if the luminance of the source exceeds $10^4 \text{ cd}\cdot\text{m}^{-2}$		P
4.3	Hazard exposure limits		P
4.3.1	Actinic UV hazard exposure limit for the skin and eye		P
	The exposure limit for effective radiant exposure is $30 \text{ J}\cdot\text{m}^{-2}$ within any 8-hour period		P
	To protect against injury of the eye or skin from ultraviolet radiation exposure produced by a broadband source, the effective integrated spectral irradiance, $E_s$ , of the light source shall not exceed the levels defined by:		P
	$E_s \cdot t = \sum_{200}^{400} \sum_t E_\lambda(\lambda, t) \cdot S_{UV}(\lambda) \cdot \Delta t \cdot \Delta\lambda \leq 30 \text{ J}\cdot\text{m}^{-2}$		P
	The permissible time for exposure to ultraviolet radiation incident upon the unprotected eye or skin shall be computed by:		P
	$t_{\max} = \frac{30}{E_s} \text{ s}$		P
4.3.2	Near-UV hazard exposure limit for eye		P
	For the spectral region 315 nm to 400 nm (UV-A) the total radiant exposure to the eye shall not exceed $10000 \text{ J}\cdot\text{m}^{-2}$ for exposure times less than 1000 s. For exposure times greater than 1000 s (approximately 16 minutes) the UV-A irradiance for the unprotected eye, $E_{UVA}$ , shall not exceed $10 \text{ W}\cdot\text{m}^{-2}$ .		P
	The permissible time for exposure to ultraviolet		P

EN 62471			
Clause	Requirement + Test	Result - Remark	Verdict
	radiation incident upon the unprotected eye for time less than 1000 s, shall be computed by:		
	$t_{\max} \leq \frac{10\ 000}{E_{\text{UVA}}} \text{ s}$		P
4.3.3	Retinal blue light hazard exposure limit		P
	To protect against retinal photochemical injury from chronic blue-light exposure, the integrated spectral radiance of the light source weighted against the blue-light hazard function, $B(\lambda)$ , i.e., the blue-light weighted radiance, $L_B$ , shall not exceed the levels defined by:		P
	$L_B \cdot t = \sum_{300}^{700} \sum_t L_\lambda(\lambda, t) \cdot B(\lambda) \cdot \Delta t \cdot \Delta\lambda \leq 10^6 \text{ J} \cdot \text{m}^{-2} \cdot \text{sr}^{-1}$	fort $\leq 10^4 \text{ s}$ $t_{\max} = \frac{10^6}{L_B}$	P
	$L_B = \sum_{300}^{700} L_\lambda \cdot B(\lambda) \cdot \Delta\lambda \leq 100 \text{ W} \cdot \text{m}^{-2} \cdot \text{sr}^{-1}$	fort $> 10^4 \text{ s}$	P
4.3.4	Retinal blue light hazard exposure limit - small source		N/A
	Thus the spectral irradiance at the eye $E_\lambda$ , weighted against the blue-light hazard function $B(\lambda)$ shall not exceed the levels defined by:		N/A
	$E_B \cdot t = \sum_{300}^{700} \sum_t E_\lambda(\lambda, t) \cdot B(\lambda) \cdot \Delta t \cdot \Delta\lambda \leq 100 \text{ J} \cdot \text{m}^{-2}$		N/A
	$E_B = \sum_{300}^{700} E_\lambda \cdot B(\lambda) \cdot \Delta\lambda \leq 1 \text{ W} \cdot \text{m}^{-2}$		N/A
4.3.5	Retinal thermal hazard exposure limit		P
	To protect against retinal thermal injury, the integrated spectral radiance of the light source, $L_\lambda$ , weighted by the burn hazard weighting function $R(\lambda)$ (from Figure 4.2 and Table 4.2), i.e., the burn hazard weighted radiance, shall not exceed the levels defined by:		P

EN 62471			
Clause	Requirement + Test	Result - Remark	Verdict
	$L_R = \sum_{380}^{1400} L_\lambda \cdot R(\lambda) \cdot \Delta\lambda \leq \frac{50\,000}{\alpha \cdot t^{0,25}} \quad W \cdot m^{-2} \cdot sr^{-1}$	(10 μs ≤ t ≤ 10 s)	P
4.3.6	Retinal thermal hazard exposure limit – weak visual stimulus		P
	For an infrared heat lamp or any near-infrared source where a weak visual stimulus is inadequate to activate the aversion response, the near infrared (780 nm to 1400 nm) radiance, $L_{IR}$ , as viewed by the eye for exposure times greater than 10 s shall be limited to:		P
	$L_{IR} = \sum_{780}^{1400} L_\lambda \cdot R(\lambda) \cdot \Delta\lambda \leq \frac{6\,000}{\alpha} \quad W \cdot m^{-2} \cdot sr^{-1}$	t > 10 s	P
4.3.7	Infrared radiation hazard exposure limits for the eye		P
	The avoid thermal injury of the cornea and possible delayed effects upon the lens of the eye (cataractogenesis), ocular exposure to infrared radiation, $E_{IR}$ , over the wavelength range 780 nm to 3000 nm, for times less than 1000 s, shall not exceed:		P
	$E_{IR} = \sum_{780}^{3000} E_\lambda \cdot \Delta\lambda \leq 18\,000 \cdot t^{-0,75} \quad W \cdot m^{-2}$	t ≤ 1000 s	P
	For times greater than 1000 s the limit becomes:		P
	$E_{IR} = \sum_{780}^{3000} E_\lambda \cdot \Delta\lambda \leq 100 \quad W \cdot m^{-2}$	t > 1000 s	P
4.3.8	Thermal hazard exposure limit for the skin		P
	Visible and infrared radiant exposure (380 nm to 3000 nm) of the skin shall be limited to:		P
	$E_H \cdot t = \sum_{380}^{3000} \sum_{\lambda} E_\lambda(\lambda, t) \cdot \Delta\lambda \cdot \Delta t \leq 20\,000 \cdot t^{0,25} \quad J \cdot m^{-2}$		P

5	MEASUREMENT OF LAMPS AND LAMP SYSTEMS	P
5.1	Measurement conditions	P



EN 62471			
Clause	Requirement + Test	Result - Remark	Verdict
	Measurement conditions shall be reported as part of the evaluation against the exposure limits and the assignment of risk classification.		P
5.1.1	Lamp ageing (seasoning)		N/A
	Seasoning of lamps shall be done as stated in the appropriate IEC lamp standard.		N/A
5.1.2	Test environment		P
	For specific test conditions, see the appropriate IEC lamp standard or in absence of such standards, the appropriate national standards or manufacturer's recommendations.	Temperature maintained at $25\pm1^{\circ}\text{C}$ , Relative humidity shall be maintained to less than 65%; Airflow shall be minimized when measuring	P
5.1.3	Extraneous radiation		P
	Careful checks should be made to ensure that extraneous sources of radiation and reflections do not add significantly to the measurement results.		P
5.1.4	Lamp operation		N/A
	Operation of the test lamp shall be provided in accordance with:		N/A
	– the appropriate IEC lamp standard, or		N/A
	– the manufacturer's recommendation		N/A
5.1.5	Lamp system operation		N/A
	The power source for operation of the test lamp shall be provided in accordance with:		N/A
	– the appropriate IEC standard, or		N/A
	– the manufacturer's recommendation		N/A
5.2	Measurement procedure		P
5.2.1	Irradiance measurements		P
	Minimum aperture diameter 7mm.		P
	Maximum aperture diameter 50 mm.		P

EN 62471			
Clause	Requirement + Test	Result - Remark	Verdict
	The measurement shall be made in that position of the beam giving the maximum reading.		P
	The measurement instrument is adequate calibrated.		P
5.2.2	Radiance measurements		P
5.2.2.1	Standard method		P
	The measurements made with an optical system.		P
	The instrument shall be calibrated to read in absolute radiant power per unit receiving area and per unit solid angle to acceptance averaged over the field of view of the instrument.		P
5.2.2.2	Alternative method		N/A
	Alternatively to an imaging radiance set-up, an irradiance measurement set-up with a circular field stop placed at the source can be used to perform radiance measurements.		N/A
5.2.3	Measurement of source size		P
	The determination of $\alpha$ , the angle subtended by a source, requires the determination of the 50% emission points of the source.		P
5.2.4	Pulse width measurement for pulsed sources	Continuous wave lamps	N/A
	The determination of $\Delta t$ , the nominal pulse duration of a source, requires the determination of the time during which the emission is $> 50\%$ of its peak value.		N/A
5.3	Analysis methods		P
5.3.1	Weighting curve interpolations		P
	To standardize interpolated values, use linear interpolation on the log of given values to obtain intermediate points at the wavelength intervals desired.		P
5.3.2	Calculations		P
	The calculation of source hazard values shall be performed by weighting the spectral scan by the appropriate function and calculating the total weighted		P

EN 62471			
Clause	Requirement + Test	Result - Remark	Verdict
	energy.		
5.3.3	Measurement uncertainty		P
	The quality of all measurement results must be quantified by an analysis of the uncertainty.		P

6	<b>LAMP CLASSIFICATION</b>		N/A
	For the purposes of this standard it was decided that the values shall be reported as follows:	see table 6.1	N/A
	<ul style="list-style-type: none"> <li>– for lamps intended for general lighting service, the hazard values shall be reported as either irradiance or radiance values at a distance which produces an illuminance of 500 lux, but not at a distance less than 200 mm</li> </ul>	At a distance which produces an illuminance of 500 lux	N/A
	<ul style="list-style-type: none"> <li>– for all other light sources, including pulsed lamp sources, the hazard values shall be reported at a distance of 200 mm</li> </ul>		N/A
6.1	Continuous wave lamps		P
6.1.1	Exempt Group		N/A
	In the exempt group are lamps, which does not pose any photobiological hazard. The requirement is met by any lamp that does not pose:		N/A
	<ul style="list-style-type: none"> <li>– an actinic ultraviolet hazard (<math>E_s</math>) within 8-hours exposure (30000 s), nor</li> </ul>		N/A
	<ul style="list-style-type: none"> <li>– a near-UV hazard (<math>E_{UVA}</math>) within 1000 s, (about 16 min), nor</li> </ul>		N/A
	<ul style="list-style-type: none"> <li>– a retinal blue-light hazard (<math>L_B</math>) within 10000 s (about 2,8 h), nor</li> </ul>		N/A
	<ul style="list-style-type: none"> <li>– a retinal thermal hazard (<math>L_R</math>) within 10 s, nor</li> </ul>		N/A
	<ul style="list-style-type: none"> <li>– an infrared radiation hazard for the eye (<math>E_{IR}</math>) within 1000 s</li> </ul>		N/A
6.1.2	Risk Group 1 (Low-Risk)		P
	In this group are lamps, which exceeds the limits for the		P

EN 62471			
Clause	Requirement + Test	Result - Remark	Verdict
	exempt group but that does not pose: <ul style="list-style-type: none"> <li>– an actinic ultraviolet hazard (<math>E_s</math>) within 10000 s, nor</li> <li>– a near ultraviolet hazard (<math>E_{UVA}</math>) within 300 s, nor</li> <li>– a retinal blue-light hazard (<math>L_B</math>) within 100 s, nor</li> <li>– a retinal thermal hazard (<math>L_R</math>) within 10 s, nor</li> <li>– an infrared radiation hazard for the eye (<math>E_{IR}</math>) within 100 s</li> </ul>		P
	Lamps that emit infrared radiation without a strong visual stimulus and do not pose a near-infrared retinal hazard ( $L_{IR}$ ), within 100 s are in Risk Group 1.		P
6.1.3	Risk Group 2 (Moderate-Risk)		N/A
	This requirement is met by any lamp that exceeds the limits for Risk Group 1, but that does not pose: <ul style="list-style-type: none"> <li>– an actinic ultraviolet hazard (<math>E_s</math>) within 1000 s exposure, nor</li> <li>– a near ultraviolet hazard (<math>E_{UVA}</math>) within 100 s, nor</li> <li>– a retinal blue-light hazard (<math>L_B</math>) within 0,25 s (aversion response), nor</li> <li>– a retinal thermal hazard (<math>L_R</math>) within 0,25 s (aversion response), nor</li> <li>– an infrared radiation hazard for the eye (<math>E_{IR}</math>) within 10 s</li> </ul>		N/A
	Lamps that emit infrared radiation without a strong visual stimulus and do not pose a near-infrared retinal hazard ( $L_{IR}$ ), within 10 s are in Risk Group 2.		N/A
6.1.4	Risk Group 3 (High-Risk)		N/A
	Lamps which exceed the limits for Risk Group 2 are in Group 3.		N/A
6.2	Pulsed lamps		N/A
	Pulse lamp criteria shall apply to a single pulse and to any group of pulses within 0,25 s.	Continuous wave lamps	N/A

EN 62471			
Clause	Requirement + Test	Result - Remark	Verdict
	A pulsed lamp shall be evaluated at the highest nominal energy loading as specified by the manufacturer.		N/A
	The risk group determination of the lamp being tested shall be made as follows:		N/A
	<ul style="list-style-type: none"> <li>– a lamp that exceeds the exposure limit shall be classified as belonging to Risk Group 3 (High-Risk)</li> </ul>		N/A
	<ul style="list-style-type: none"> <li>– for single pulsed lamps, a lamp whose weighted radiant exposure or weighted radiance does is below the EL shall be classified as belonging to the Exempt Group</li> </ul>		N/A
	<ul style="list-style-type: none"> <li>– for repetitively pulsed lamps, a lamp whose weighted radiant exposure or weighted radiance dose is below the EL, shall be evaluated using the continuous wave risk criteria discussed in clause 6.1, using time averaged values of the pulsed emission</li> </ul>		N/A

<b>Table 4.1</b> Spectral weighting function for assessing ultraviolet hazards for skin and eye				--
<b>Wavelength<sup>1</sup></b> <b><math>\lambda</math>, nm</b>	<b>UV hazard function</b> <b><math>S_{UV}(\lambda)</math></b>	<b>Wavelength</b> <b><math>\lambda</math>, nm</b>	<b>UV hazard function <math>S_{UV}(\lambda)</math></b>	
200	0,030	313*	0,006	
205	0,051	315	0,003	
210	0,075	316	0,0024	
215	0,095	317	0,0020	
220	0,120	318	0,0016	
225	0,150	319	0,0012	
230	0,190	320	0,0010	
235	0,240	322	0,00067	
240	0,300	323	0,00054	
245	0,360	325	0,00050	
250	0,430	328	0,00044	
254*	0,500	330	0,00041	
255	0,520	333*	0,00037	
260	0,650	335	0,00034	
265	0,810	340	0,00028	
270	1,000	345	0,00024	
275	0,960	350	0,00020	
280*	0,880	355	0,00016	
285	0,770	360	0,00013	
290	0,640	365*	0,00011	
295	0,540	370	0,000093	
297*	0,460	375	0,000077	
300	0,300	380	0,000064	
303*	0,120	385	0,000053	

<b>Table 4.1</b> Spectral weighting function for assessing ultraviolet hazards for skin and eye				--
305	0,060	390	0,000044	
308	0,026	395	0,000036	
310	0,015	400	0,000030	

<sup>1</sup> Wavelengths chosen are representative; other values should be obtained by logarithmic interpolation at intermediate wavelengths.

\* Emission lines of a mercury discharge spectrum.

<b>Table 4.2</b>	Spectral weighting functions for assessing retinal hazards from broadband optical sources		--
<b>Wavelength</b> <b>nm</b>	<b>Blue-light hazard function</b> <b>B (λ)</b>	<b>Burn hazard function</b> <b>R (λ)</b>	
300	0,01	0,1	
305	0,01	0,1	
310	0,01	0,1	
315	0,01	0,1	
320	0,01	0,1	
325	0,01	0,1	
330	0,01	0,1	
335	0,01	0,1	
340	0,01	0,1	
345	0,01	0,1	
350	0,01	0,1	
355	0,01	0,1	
360	0,01	0,1	
365	0,01	0,1	
370	0,01	0,1	
375	0,01	0,1	
380	0,01	0,1	
385	0,013	0,13	
390	0,025	0,25	
395	0,05	0,5	
400	0,10	1,0	
405	0,20	2,0	
410	0,40	4,0	
415	0,80	8,0	
420	0,90	9,0	
425	0,95	9,5	
430	0,98	9,8	
435	1,00	10,0	
440	1,00	10,0	
445	0,97	9,7	
450	0,94	9,4	

<b>Table 4.2</b> Spectral weighting functions for assessing retinal hazards from broadband optical sources		
455	0,90	9,0
460	0,80	8,0
465	0,70	7,0
470	0,62	6,2
475	0,55	5,5
480	0,45	4,5
485	0,40	4,0
490	0,22	2,2
495	0,16	1,6
500-600	$10^{[(450-\lambda)/50]}$	1,0
600-700	0,001	1,0
700-1050		$10^{[(700-\lambda)/500]}$
1050-1150		0,2
1150-1200		$0,2 \cdot 10^{0,02(1150-\lambda)}$
1200-1400		0,02

Table 5.4   Summary of the ELs for the surface of the skin or cornea (irradiance based values)   --					
Hazard Name	Relevant equation	Wavelength range nm	Exposure duration sec	Limiting aperture rad (deg)	EL in terms of constant irradiance W·m⁻²
Actinic UV skin & eye	$E_s = \sum E_\lambda \cdot S(\lambda) \cdot \Delta\lambda$	200 – 400	< 30000	1,4 (80)	30/t
Eye UV-A	$E_{UVA} = \sum E_\lambda \cdot \Delta\lambda$	315 – 400	$\leq 1000$ $> 1000$	1,4 (80)	10000/t 10
Blue-light small source	$E_B = \sum E_\lambda \cdot B(\lambda) \cdot \Delta\lambda$	300 – 700	$\leq 100$ $> 100$	< 0,011	100/t 1,0
Eye IR	$E_{IR} = \sum E_\lambda \cdot \Delta\lambda$	780 – 3000	$\leq 1000$ $> 1000$	1,4 (80)	18000/t <sup>0,75</sup> 100
Skin thermal	$E_H = \sum E_\lambda \cdot \Delta\lambda$	380 – 3000	< 10	$2\pi$ sr	20000/t <sup>0,75</sup>

Table 5.5   Summary of the ELs for the retina (radiance based values)   --					
Hazard Name	Relevant equation	Wavelength range nm	Exposure duration sec	Field of view radians	EL in terms of constant radiance W·m⁻²·sr⁻¹)
Blue light	$L_B = \sum L_\lambda \cdot B(\lambda) \cdot \Delta\lambda$	300 – 700	0,25 – 10 10-100 100-10000 $\geq 10000$	0,011· $\sqrt{t/10}$ 0,011 0,0011· $\sqrt{t}$ 0,1	10 <sup>6</sup> /t 10 <sup>6</sup> /t 10 <sup>6</sup> /t 100
Retinal thermal	$L_R = \sum L_\lambda \cdot R(\lambda) \cdot \Delta\lambda$	380 – 1400	< 0,25 0,25 – 10	0,0017 0,011· $\sqrt{t/10}$	50000/( $\alpha \cdot t^{0,25}$ ) 50000/( $\alpha \cdot t^{0,25}$ )
Retinal thermal (weak visual stimulus)	$L_{IR} = \sum L_\lambda \cdot R(\lambda) \cdot \Delta\lambda$	780 – 1400	> 10	0,011	6000/ $\alpha$



Report No.: RKEYS251224263

Date: Jan. 28, 2026

Page 17 of 21

Table 6.1   Emission limits for risk groups of continuous wave lamps (Base on IEC 62471:2006)							P	
Risk	Action spectrum	Symbol	Units	Emission Measurement				
				Exempt		Low risk		Mod risk
				Limit	Result	Limit	Result	Limit
Actinic UV	SUV( $\lambda$ )	Es	W•m <sup>-2</sup>	0,001	--	0.003	0.004E+00	0.03
Near UV		EUVA	W•m <sup>-2</sup>	0,33	--	33	2.15E+01	100
Blue light	B( $\lambda$ )	L <sub>B</sub>	W•m <sup>-2</sup> •sr <sup>-1</sup>	100	--	10000	5.16E+01	4000000
Blue light, small source	B( $\lambda$ )	E <sub>B</sub>	W•m <sup>-2</sup>	--	--	--	--	--
Retinal thermal	R( $\lambda$ )	L <sub>R</sub>	W•m <sup>-2</sup> •sr <sup>-1</sup>	28000/ $\alpha$	--	28000/ $\alpha$	1.64E+04	71000/ $\alpha$
Retinal thermal, weak visual stimulus**	R( $\lambda$ )	L <sub>IR</sub>	W•m <sup>-2</sup> •sr <sup>-1</sup>	6000/ $\alpha$	--	6000/ $\alpha$	3.21E-01	6000/ $\alpha$
IR radiation, eye		E <sub>IR</sub>	W•m <sup>-2</sup>	100	--	570	3.25E-05	3200

Remark:

Angular subtense of apparent source,  $\alpha=50.1\text{mrad}$



Report No.: RKEYS251224263

Date: Jan. 28, 2026

Page 18 of 21

<b>Table 6.1</b>	Emission limits for risk groups of continuous wave lamps (Base on IEC 62471:2006)	P
* Small source defined as one with $0 < 0,011$ radian. Averaging field of view at 10000 s is 0,1 radian.		
** Involves evaluation of non-GLS source		


**Photo documentation**

<input checked="" type="checkbox"/> front	
<input type="checkbox"/> rear	
<input type="checkbox"/> right side	
<input type="checkbox"/> left side	
<input type="checkbox"/> top	
<input type="checkbox"/> bottom	
<input type="checkbox"/> internal	

<input type="checkbox"/> front	
<input type="checkbox"/> rear	
<input type="checkbox"/> right side	
<input type="checkbox"/> left side	
<input type="checkbox"/> top	
<input type="checkbox"/> bottom	
<input type="checkbox"/> internal	

- front
- rear
- right side
- left side
- top
- bottom
- internal



- front
- rear
- right side
- left side
- top
- bottom
- internal



- front
- rear
- right side
- left side
- top
- bottom
- internal



\*\*\* End of Report \*\*\*